


Captive Screw Type 5 4-40 Thread



Create a part number:

Length	Material	Finish
FCXXXX	XX	XX

Captive Screws - 4-40 Thread			
✓	FCXXXX	Length (L)	S.L. REF
	FC0896	5/16	1/16
	FC0897	3/8	1/8
	FC0898	7/16	3/16
	FC0899	1/2	1/4
	FC0900	9/16	5/16
	FC0901	5/8	3/8
	FC0902	11/16	7/16
	FC0903	3/4	1/2
	FC0904	13/16	9/16
	FC0905	7/8	5/8
	FC0906	15/16	11/16
	FC0907	1	3/4

Material		
✓ Material Code (XX)		
	B	Brass
	S	Steel
	SS	Stainless Steel

✓ Compatible Finish (XX)		
	B, S, SS	0 - Plain
	B, S	5 - Nickel Plate (QQ-N-290)
	B, S	12 - Zinc Clear (ASTM-B-633)
	B, S	16 - Electro Tin (MIL-T-10727 TYPE 1)
	SS	20 - Passivation (MIL-F-14072D)
	B, S, SS	26 - Black Oxide
	B, S	28 - Zinc Yellow (ASTM-B-633)

Tolerances
Unless otherwise Specified
 .xxx +/- .005
 .xx +/- .010
 Angular +/- 1 Degree
 Linear +/- .005
Break all sharp edges



Source Control Drawing:
 To be produced by
 Fascomp Electronic Hardware

This document is the property of Fascomp Inc. and shall not be reproduced, distributed, or used as a basis for manufacturing without written permission from Fascomp Inc.