

# 1/8 Square Female Standoff



Hex Code Table		
✓	FCXXXX	Length (L)
	FC2450	1/8
	FC2451	3/16
	FC2452	1/4
	FC2453	5/16
	FC2454	3/8
	FC2455	7/16
	FC2456	1/2
	FC2457	9/16
	FC2458	5/8
	FC2459	11/16
	FC2460	3/4
	FC2461	13/16
	FC2462	7/8
	FC2463	15/16
	FC2464	1
	FC2465	1-1/16
	FC2466	1-1/8
	FC2467	1-3/16
	FC2468	1-1/4
	FC2469	1-5/16
	FC2470	1-3/8
	FC2471	1-7/16
	FC2472	1-1/2
	FC2473	1-9/16
	FC2474	1-5/8
	FC2475	1-11/16
	FC2476	1-3/4
	FC2477	1-13/16
	FC2478	1-7/8
	FC2479	1-15/16
	FC2480	2

### Create a part number:

Length	Thread	Material	Finish
FCXXXX	XXX	XX	XX
_____ - _____ - _____ - _____			

Thread				Material	
✓ Thread Code (XXX)	Tapped Thru		Longer Parts Blind Tap Depth	✓ Material Code (XX)	
	A, B, S	SS			
080	3/8	1/4	3/16	A	Aluminum
256	3/4	5/8	3/16	B	Brass
				S	Steel
				SS	Stainless Steel
				N	Nylon

✓ Compatible Finish (XX)	
A, B, S, SS	0 - Plain
B, S	5 - Nickel Plate (QQ-N-290)
A	6 - Iridite #14 Gold (MIL-C-5541E)
A	7 - Iridite Clear (MIL-C-5541E)
A	9 - Alodine 1200
B, S	12 - Zinc Clear (ASTM-B-633)
B, S	16 - Electro Tin (MIL-T-10727 TYPE 1)
SS	20 - Passivation (MIL-F-14072D)
A	22 - Clear Anodize (MIL-A-8625-TYPE2) (Sulphuric) Hot Water Seal (Clear)
A	24 - Black Anodize (MIL-A-8625)
B, S, SS	26 - Black Oxide
B, S	28 - Zinc Yellow (ASTM-B-633)



Source Control Drawing:  
To be produced by  
Fascomp Electronic Hardware

**Tolerances Unless otherwise Specified**  
 .xxx +/- .005  
 .xx +/- .010  
 Angular +/- 1 Degree  
 Linear +/- .005  
**Break all sharp edges**

This document is the property of Fascomp Inc. and shall not be reproduced, distributed or used as a basis for manufacturing without written permission from Fascomp Inc.