

3/8 Square Female Standoff

Hex Code Table		
✓ FCXXXX	Length (L)	
FC2662	1/8	
FC2663	3/16	
FC2664	1/4	
FC2665	5/16	
FC2666	3/8	
FC2667	7/16	
FC2668	1/2	
FC2669	9/16	
FC2670	5/8	
FC2671	11/16	
FC2672	3/4	
FC2673	13/16	
FC2674	7/8	
FC2675	15/16	
FC2676	1	
FC2677	1-1/16	
FC2678	1-1/8	
FC2679	1-3/16	
FC2680	1-1/4	
FC2681	1-5/16	
FC2682	1-3/8	
FC2683	1-7/16	
FC2684	1-1/2	
FC2685	1-9/16	
FC2686	1-5/8	
FC2687	1-11/16	
FC2688	1-3/4	
FC2689	1-13/16	
FC2690	1-7/8	
FC2691	1-15/16	
FC2692	2	
FC2693	2-1/8	
FC2694	2-1/4	
FC2695	2-3/8	
FC2696	2-1/2	
FC2697	2-5/8	
FC2698	2-3/4	
FC2699	2-7/8	
FC2700	3	
FC2701	3-1/4	
FC2702	3-1/2	
FC2703	3-3/4	
FC2704	4	
FC2705	4-1/4	
FC2706	4-1/2	
FC2707	4-3/4	
FC2708	5	
FC2709	5-1/4	
FC2710	5-1/2	
FC2711	5-3/4	
FC2712	6	



Create a part number:

Length	Thread	Material	Finish
FCXXXX	XXX	XX	XX
_____ - _____ - _____ - _____			

✓	Thread			
	Thread Code (XXX)	Tapped Thru		Longer Parts
		A, B, S	SS	Blind Tap Depth
632	1	1	3/8	
832	1	1	7/16	
1032	1-1/8	1	1/2	
1224	1-1/8	1	1/2	
2520	1-1/4	1-1/4	5/8	

Material	
✓	Material Code (XX)
A	Aluminum
B	Brass
S	Steel
SS	Stainless Steel
N	Nylon

Aluminum (A), Brass (B), Steel (S), Stainless Steel (SS)

Tolerances Unless otherwise Specified
 .xxx +/- .005
 .xx +/- .010
 Angular +/- 1 Degree
 Linear +/- .005
Break all sharp edges

✓ Compatible Finish (XX)	
A, B, S, SS	0 - Plain
B, S	5 - Nickel Plate (QQ-N-290)
A	6 - Iridite #14 Gold (MIL-C-5541E)
A	7 - Iridite Clear (MIL-C-5541E)
A	9 - Alodine 1200
B, S	12 - Zinc Clear (ASTM-B-633)
B, S	16 - Electro Tin (MIL-T-10727 TYPE 1)
SS	20 - Passivation (MIL-F-14072D)
A	22 - Clear Anodize (MIL-A-8625-TYPE2) (Sulphuric) Hot Water Seal (Clear)
A	24 - Black Anodize (MIL-A-8625)
B, S, SS	26 - Black Oxide
B, S	28 - Zinc Yellow (ASTM-B-633)



Source Control Drawing:
 To be produced by
 Fascomp Electronic Hardware

This document is the property of Fascomp Inc. and shall not be reproduced, distributed or used as a basis for manufacturing without written permission from Fascomp Inc.