




For Tap Thru and Blind Tap information see chart

| Tapped Thru up to and including these lengths | Longer Lengths |
|-----------------------------------------------|----------------|
|-----------------------------------------------|----------------|

| Thread | Aluminum, Brass, Steel & Nylon | Stainless Steel | Tap Each End |
|--------|--------------------------------|-----------------|--------------|
| 0-80   | .375                           | .250            | .187         |
| 2-56   | .750                           | .625            | .187         |
| 4-40   | 1.00                           | .750            | .250         |
| 6-32   | 1.00                           | 1.00            | .375         |
| 8-32   | 1.00                           | 1.00            | .437         |
| 10-32  | 1.125                          | 1.00            | .500         |
| 12-24  | 1.125                          | 1.00            | .500         |
| 25-20  | 1.250                          | 1.250           | .625         |

All base materials are RoHS compliant

|                                                                                                                                                                                                                                 |                                                                                                                                                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Drawing not to scale                                                                                                                                                                                                            | Title: Round Female Standoff                                                                                                                                                                                        |
| Break all sharp edges on outside diameters                                                                                                                                                                                      | Part Number: FC1638-440-SS                                                                                                                                                                                          |
| All base materials are RoHS compliant                                                                                                                                                                                           | Material: Stainless Steel                                                                                                                                                                                           |
| Tolerances<br>(Unless Specified)<br><u>Decimal</u> .XXX ± .005<br>.XX ± .010<br><br><u>Fraction</u> ± .005<br><br><u>Angle</u> ± 3°<br><br><u>Millimeters</u> ± .13<br><br><u>Nylon</u> ± .010<br><br><u>Metric Nylon</u> ± .25 | Finish: Plain<br><br><br><br>1235 Tradeport Drive, Orlando, FL 32824<br>Tel: 407-226-2112 Fax: 407-226-3370<br>www.Fascomp.com |