



For Tap Thru and Blind Tap information see chart

| Thread | Tapped Thru up to and including these lengths |                 | Longer Lengths |
|--------|---|-----------------|----------------|
|        | Aluminum, Brass, Steel & Nylon                | Stainless Steel | Tap Each End   |
| 0-80   | .375  | .250            | .187           |
| 2-56   | .750  | .625            | .187           |
| 4-40   | 1.00  | .750            | .250           |
| 6-32   | 1.00  | 1.00            | .375           |
| 8-32   | 1.00  | 1.00            | .437           |
| 10-32  | 1.125   | 1.00            | .500           |
| 12-24  | 1.125   | 1.00            | .500           |
| 25-20  | 1.250   | 1.250           | .625           |

All base materials are RoHS compliant

|   |                              |
|---|------------------------------|
| Drawing not to scale  | Title: Round Female Standoff |
| Break all sharp edges on outside diameters  | Part Number: FC1683-832-A    |
| All base materials are RoHS compliant   | Material: Aluminum           |
| Tolerances<br>(Unless Specified)<br><u>Decimal</u> .XXX ± .005<br>.XX ± .010<br><br><u>Fraction</u> ± .005<br><br><u>Angle</u> ± 3°<br><br><u>Millimeters</u> ± .13<br><br><u>Nylon</u> ± .010<br><br><u>Metric Nylon</u> ± .25 | Finish: Plain                |
|   |                              |
| 1235 Tradeport Drive, Orlando, FL 32824<br>Tel: 407-226-2112 Fax: 407-226-3370<br>www.Fascomp.com   |                              |