


## 5/8



Tapped Thru up to and including

these lengths

Longer Lengths

For Tap Thru and Blind Tap information see chart

| Thread | Aluminum, Brass,<br>Steel & Nylon | Stainless Steel | Tap Each End |
|--------|-----------------------------------|-----------------|--------------|
| 0-80   | .375                              | .250            | .187         |
| 2-56   | .750                              | .625            | .187         |
| 4-40   | 1.00                              | .750            | .250         |
| 6-32   | 1.00                              | 1.00            | .375         |
| 8-32   | 1.00                              | 1.00            | .437         |
| 10-32  | 1.125                             | 1.00            | .500         |
| 12-24  | 1.125                             | 1.00            | .500         |
| 25-20  | 1.250                             | 1.250           | .625         |

| All base materials are RoHS compliant |
|---------------------------------------|
|---------------------------------------|

| Drawing not to scale                                    | Title: Hex Female Standoff  |  |
|---|---|--|
| Break all sharp edges on outside diameters              | Part Number: FC2173-1032-SS   |  |
| All base materials are RoHS compliant                   | Material: Stainless Steel   |  |
| Tolerances<br>(Unless Specified)<br>Decimal .XXX ± .005 | Finish: Plain   |  |
| .XX ± .010  |   |  |
| <u>Fraction</u> ± .005                                  | "The Good Guys"   |  |
| Angle ± 3°  | electronic hardware   |  |
| <u>Millimeters</u> ± .13                                |   |  |
| <u>Nylon</u> ± .010                                     |   |  |
| <u>Metric Nylon</u> ± .25                               | 1235 Tradeport Drive, Orlando, FL 32824<br>Tel: 407-226-2112 Fax: 407-226-3370<br>www.Fascomp.com |  |