

*Short Lengths Minimum Internal Thread Depth									
Body Lengths in Decimal									
Thread	.187	.250	.312	.375	.437	.500	.562	.625	.750
2-56	.095	.150							
4-40	.100	.150	.200						
6-32	.090	.130	.190	.250	.300				
8-32	.090	.130	.190	.250	.300	.355			
10-32	.090	.125	.190	.250	.300	.355	.434	.475	
12-24	.070	.110	.160	.195	.250	.335	.424	.465	
25-20	.060	.090	.135	.160	.250	.310	.365	.430	.553
31-18	.060	.080	.125	.150	.220	.280	.335	.400	.475

All base materials are	RoHS compliant
_	_

Drawing not to scale	Title: Hex Male-Female Standoff			
Break all sharp edges on outside diameters	Part Number: FC4546-832-SS			
All base materials are RoHS compliant	Material: Stainless Steel			
Tolerances (Unless Specified) Decimal .XXX ± .005	Finish: Plain			
.XX ± .010				
<u>Fraction</u> ± .005	"The Good Guys"			
Angle ± 3°	electronic hardware			
Millimeters ± .13				
<u>Nylon</u> ± .010				
<u>Metric Nylon</u> ± .25	1235 Tradeport Drive, Orlando, FL 32824 Tel: 407-226-2112 Fax: 407-226-3370 www.Fascomp.com			