



For Tap Thru and Blind Tap information see chart

| Thread   | Tapped Thru up to and including these lengths |                 | Longer Lengths |
|----------|---|-----------------|----------------|
|          | Aluminum, Brass, Steel & Nylon                | Stainless Steel |                |
| M2x0.45  | 19  | 16              | Tap Each End   |
| M3x0.5   | 25  | 19              | 4.7            |
| M3.5x0.6 | 25  | 25              | 6.3            |
| M4x0.7   | 25  | 25              | 9.5            |
| M5x0.8   | 28  | 25              | 11.1           |
| M6x1.0   | 31  | 31              | 12.7           |
| M8x1.25  | 31  | 41              | 16             |

All base materials are RoHS compliant

|  |   |
|--|---|
| Drawing not to scale   | Title: Metric Hex Female Standoff   |
| Break all sharp edges on outside diameters                                   | Part Number: FM1264-3005-SS   |
| All base materials are RoHS compliant  | Material: Stainless Steel   |
| Tolerances<br>(Unless Specified)<br><u>Decimal</u> .XXX ± .005<br>.XX ± .010 | Finish: Plain   |
| <u>Fraction</u> ± .005   |   |
| <u>Angle</u> ± 3°  |   |
| <u>Millimeters</u> ± .13   |   |
| <u>Nylon</u> ± .010  |   |
| <u>Metric Nylon</u> ± .25  | 1235 Tradeport Drive, Orlando, FL 32824<br>Tel: 407-226-2112 Fax: 407-226-3370<br>www.Fascomp.com |