



For Tap Thru and Blind Tap information see chart

|   |                |
|---|----------------|
| Tapped Thru up to and including these lengths | Longer Lengths |
|---|----------------|

| Thread   | Aluminum, Brass, Steel & Nylon | Stainless Steel | Tap Each End |
|----------|--------------------------------|-----------------|--------------|
| M2x0.45  | 19                             | 16              | 4.7          |
| M3x0.5   | 25                             | 19              | 6.3          |
| M3.5x0.6 | 25                             | 25              | 9.5          |
| M4x0.7   | 25                             | 25              | 11.1         |
| M5x0.8   | 28                             | 25              | 12.7         |
| M6x1.0   | 31                             | 31              | 16           |
| M8x1.25  | 31                             | 41              | 16           |

All base materials are RoHS compliant

|   |                                   |
|---|-----------------------------------|
| Drawing not to scale  | Title: Metric Hex Female Standoff |
| Break all sharp edges on outside diameters  | Part Number: FM1272-3005-A        |
| All base materials are RoHS compliant   | Material: Aluminum                |
| Tolerances<br>(Unless Specified)<br><u>Decimal</u> .XXX ± .005<br>.XX ± .010<br><br><u>Fraction</u> ± .005<br><br><u>Angle</u> ± 3°<br><br><u>Millimeters</u> ± .13<br><br><u>Nylon</u> ± .010<br><br><u>Metric Nylon</u> ± .25 | Finish: Plain                     |
|   |                                   |
| 1235 Tradeport Drive, Orlando, FL 32824<br>Tel: 407-226-2112 Fax: 407-226-3370<br>www.Fascomp.com   |                                   |