



For Tap Thru and Blind Tap information see chart

| | |
|---|----------------|
| Tapped Thru up to and including these lengths | Longer Lengths |
|---|----------------|

| Thread | Aluminum, Brass, Steel & Nylon | Stainless Steel | Tap Each End |
|----------|--------------------------------|-----------------|--------------|
| M2x0.45 | 19 | 16 | 4.7 |
| M3x0.5 | 25 | 19 | 6.3 |
| M3.5x0.6 | 25 | 25 | 9.5 |
| M4x0.7 | 25 | 25 | 11.1 |
| M5x0.8 | 28 | 25 | 12.7 |
| M6x1.0 | 31 | 31 | 16 |
| M8x1.25 | 31 | 41 | 16 |

All base materials are RoHS compliant

| | |
|---|-----------------------------------|
| Drawing not to scale | Title: Metric Hex Female Standoff |
| Break all sharp edges on outside diameters | Part Number: FM1424-5008-SS |
| All base materials are RoHS compliant | Material: Stainless Steel |
| Tolerances (Unless Specified) <u>Decimal</u> .XXX ± .005 .XX ± .010 <u>Fraction</u> ± .005 <u>Angle</u> ± 3° <u>Millimeters</u> ± .13 <u>Nylon</u> ± .010 <u>Metric Nylon</u> ± .25 | Finish: Plain |
| | |
| 1235 Tradeport Drive, Orlando, FL 32824 Tel: 407-226-2112 Fax: 407-226-3370 www.Fascomp.com | |